





wartungsfrei  
maintenance-free

	b [mm]	h [mm]
<b>SPZ</b>	9,7	8,0
<b>SPA</b>	12,7	10,0
<b>SPB</b>	16,3	13,0
<b>SPC</b>	22,0	18,0

<b>SPZ</b>		<b>SPA</b>		<b>SPB</b>		<b>SPC</b>	
Richtlänge Datum length [mm]		Richtlänge Datum length [mm]		Richtlänge Datum length [mm]		Richtlänge Datum length [mm]	
1202	3350	1207	2282	1250		2000	
1212	3550	1232	2300	1320		2120	
1237		1250	2307	1400		2240	
1250		1257	2332	1500		2360	
1262		1282	2360	1600		2500	
1287		1307	2382	1700		2650	
1312		1320	2432	1800		2800	
1320		1332	2482	1900		3000	
1337		1357	2500	2000		3150	
1362		1382	2532	2120		3350	
1387		1400	2582	2240		3550	
1400		1407	2607	2360		3750	
1412		1432	2632	2500		4000	
1437		1457	2650	2650		4250	
1462		1482	2682	2800		4500	
1487		1500	2732	3000		4750	
1500		1507	2782	3150		5000	
1512		1532	2800	3350		5300	
1537		1557	2832	3550		5600	
1562		1582	2847	3750		6000	
1587		1600	2882	4000		6300	
1600		1607	2932	4250		6700	
1612		1632	2982	4500		7100	
1637		1657	3000	4750		7500	
1662		1682	3032	5000		8000	
1687		1700	3082	5300		8500	
1700		1707	3150	5600		9000	
1737		1732	3182	6000		9500	
1762		1757	3282	6300		10000	
1787		1782	3350	6700			
1800		1800	3382	7100			
1837		1807	3550	7500			
1862		1832	3750	8000			
1887		1857	4000				
1900		1882					
1937		1900					
1987		1907					
2000		1932					
2037		1957					
2120		1982					
2137		2000					
2187		2032					
2240		2057					
2287		2082					
2360		2120					
2500		2132					
2650		2182					
2800		2207					
3000		2232					
3150		2240					


Bestellbeispiel Order example	Produkt Product	Profil/Ausführung Profile and model	Richtlänge Datum length [mm]	
Optibelt RED POWER 3	Keilriemen V-Belt	SPA	1500	



**wartungsfrei  
maintenance-free**

	b [mm]	h [mm]
<b>9N</b>	9	8
<b>15N</b>	15	13
<b>25N</b>	25	23

<b>3V/9N</b>	<b>5V/15N</b>	<b>8V/25N</b>
Außenlänge Outside length [mm]	Außenlänge Outside length [mm]	Außenlänge Outside length [mm]
3V/9N 1206	5V/15N 1346	8V/25N 2540
3V/9N 1270	5V/15N 1422	8V/25N 2845
3V/9N 1346	5V/15N 1524	8V/25N 2997
3V/9N 1422	5V/15N 1600	8V/25N 3175
3V/9N 1524	5V/15N 1702	8V/25N 3353
3V/9N 1600	5V/15N 1803	8V/25N 3556
3V/9N 1702	5V/15N 1905	8V/25N 3810
3V/9N 1803	5V/15N 2032	8V/25N 4064
3V/9N 1905	5V/15N 2159	8V/25N 4318
3V/9N 2032	5V/15N 2286	8V/25N 4572
3V/9N 2159	5V/15N 2413	8V/25N 4826
3V/9N 2286	5V/15N 2540	8V/25N 5080
3V/9N 2413	5V/15N 2692	8V/25N 5385
3V/9N 2540	5V/15N 2845	8V/25N 5690
3V/9N 2692	5V/15N 2997	8V/25N 5994
3V/9N 2845	5V/15N 3175	8V/25N 6350
3V/9N 2997	5V/15N 3353	8V/25N 6731
3V/9N 3175	5V/15N 3556	8V/25N 7112
3V/9N 3353	5V/15N 3810	8V/25N 7620
3V/9N 3556	5V/15N 4064	8V/25N 8001
	5V/15N 4318	8V/25N 8509
	5V/15N 4572	8V/25N 9017
	5V/15N 4826	8V/25N 9525
	5V/15N 5080	8V/25N 10160
	5V/15N 5385	8V/25N 10795
	5V/15N 5690	8V/25N 11430
	5V/15N 5994	8V/25N 12065
	5V/15N 6350	
	5V/15N 6731	
	5V/15N 7112	
	5V/15N 7620	
	5V/15N 8001	

<b>Bestellbeispiel Order example</b>	Produkt Product	Profil/Ausführung Profile and model	Außenlänge Outside length [mm]	
Optibelt RED POWER 3	Keilriemen V-Belt	15N	2540	