




mit Aramidcord
with aramid cord

	b [mm]	h [mm]
SPB	16,3	13,0
SPC	22,0	18,0

SPB	SPC
Richtlänge Datum length ISO [mm]	Richtlänge Datum length ISO [mm]
1500	2000
1600	2120
1700	2240
1800	2360
1900	2500
2000	2650
2120	2800
2240	3000
2360	3150
2500	3350
2650	3550
2800	3750
3000	4000
3150	4250
3350	4500
3550	4750
3750	5000
4000	5300
4250	5600
4500	6000
4750	6300
5000	6700
5300	7100
5600	7500
6000	8000
6300	8500
6700	9000
7100	
7500	
8000	

Bestellbeispiel Order example	Produkt Product	Profil/Ausführung Profile and model	Richtlänge Datum length ISO [mm]
Optibelt BLUE POWER	Keilriemen V-Belt	SPB	8000









	b [mm]	h [mm]
8V/25N	25,0	23,0

8V/25N	
Außenlänge <i>Outside length</i> [mm]	
8V/25N 4064	
8V/25N 4318	
8V/25N 4572	
8V/25N 4826	
8V/25N 5080	
8V/25N 5385	
8V/25N 5690	
8V/25N 5994	
8V/25N 6350	
8V/25N 6731	
8V/25N 7112	
8V/25N 7620	
8V/25N 8001	
8V/25N 8509	

Bestellbeispiel <i>Order example</i>	Produkt <i>Product</i>	Profil/Ausführung <i>Profile and model</i>	Richtlänge <i>Datum length ISO</i> [mm]	
Optibelt BLUE POWER	Keilriemen <i>V-Belt</i>	8V/25N	9017	